



Tritex Roller Cover

Technical Information Sheet

Stock Code REPX64000K

A heat resistant roller cover designed to minimise damage to aluminium profiles during transportation immediately after the extrusion press. The roller cover is easy to fit and has a high wear resistance. Its high density ensures long service at elevated temperatures giving extended life and wear resistance.

APPLICATION	Tritex roller Cover for aluminium extrusion run out tables
COMPOSITION	Needlefelt, comprised of 100% para-aramid fibre. Needled into a continuous seamless joint less tube.
RESIN HARDENING	All Tritex rollers are available impregnated with a specially formulated resin-hardening system increasing the life and durability of the roller tube.
OPERATING TEMPERATURE	Can be operated at up to 550°C
NEEDLEFELT PARAMETERS	10 mm thick - 4.0 kg/m ² Density: .38 g/cm ³
AVAILABLE SIZES	Tritex roller covers are manufactured to fit all standard tube sizes.
LENGTH	As requested, up to 2000 mm maximum
INSTALLATION	Tritex Roller covers are manufactured to exacting standards, which allows the roller, cover to be slid onto the tube with a snug fit. Once fitted the innermost layer is designed to shrink slightly gripping the tube securely. The coefficient of friction 0.25µ on aluminium. (0.55µ on rubber, 0.15µ on steel).

Hawarden Industrial Park Manor Lane Hawarden,
Flintshire CH5 3PZ
t - 01244 520202 f - 01244 520363
sales@wirralfospray.com www.wirralfospray.com





Hawarden Industrial Park Manor Lane Hawarden,
Flintshire CH5 3PZ
t - 01244 520202 f - 01244 520363
sales@wirralfospray.com www.wirralfospray.com

