



Tritex Roller Cover

Technical Information Sheet

Stock Code REPX64000PE

A roller cover to minimise damage to aluminium profiles during transportation immediately prior to ageing. The roller cover is easy to fit, and has a high wear resistance to give a long service life.

APPLICATION Saw table roller cover for packing stations during aluminium extrusion

COMPOSITION Needlefelt, comprised of 100% polyester fibre

OPERATING TEMPERATURE 200°C maximum for continuous operation

NEEDLEFELT PARAMETERS 10 mm thick - 4.0 kg/m²

AVAILABLE SIZES	<u>Inner Diameter (mm)</u>	<u>Outer Diameter (mm)</u>
	48	68
	60	80
	76	96
	89	109
	100	120
	110	130
	130	150

LENGTH As requested, up to 1500 mm maximum

INSTALLATION Position the roller cover on the roller. Pour hot water over each end of the roller, so as to shrink the felt. Then immerse in a water bath at a temperature of at least 80°C, until the felt has shrunk to the size of the roller. Leave the roller to air dry. An alternative method is to position the felt on the roller and heat in an oven at a minimum of 80°C, but not exceeding 120°C, until the felt shrinks on to the roller.

Hawarden Industrial Park Manor Lane Hawarden,
Flintshire CH5 3PZ
t - 01244 520202 f - 01244 520363
sales@wirralfospray.com www.wirralfospray.com

