



Tritex Conveyor Strip

Technical Information Sheet

Stock Code PEPX64000PBOKRH

A heat resistant Strip designed to minimise damage to aluminium profiles during transportation immediately after the extrusion press. The strip has a high wear resistance. Its high density ensures long service at elevated temperatures giving extended life and wear resistance.

APPLICATION	Protection for Aluminium on Walking Beams and Slat Conveyors
COMPOSITION	PBO/ Kevlar Needle felt sandwich comprised of 5mm of a 100% PBO para-aramid fibre top needed to a 5mm 100% Kevlar base. Needed into a continuous seamless joint less tube.
RESIN HARDENING	All Tritex strips are available impregnated with a specially formulated resin-hardening system increasing the life and durability of the strip.
OPERATING TEMPERATURE	Can be operated at up to 600°C
NEEDLEFELT PARAMETERS	10 mm thick – 4.0 kg/m ² Density: .40 g/cm ³
AVAILABLE SIZES	Tritex strips can be manufactured to virtually any size requirement on an extrusion run out table
LENGTH	As requested, up to 1500 mm maximum
INSTALLATION	Tritex strips are manufactured to exacting standards, and are marked showing glue face.

Hawarden Industrial Park Manor Lane Hawarden,
Flintshire CH5 3PZ
t - 01244 520202 f - 01244 520363
sales@wirralfospray.com www.wirralfospray.com

